

# AE VISION®



## 36CH 960P/25CH 1080P 4HDD

- P2P cloud service, including cloud connecting, cloud monitoring,
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard
- Support megapixel HD network video preview, storage and playback;
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream, and 4 channels playback;



Model Number		N6000-36EF
Operating System		Embedded LINUX operating system
Image Code Control		Image code quality adjustable, variable bitstream and constant bitstream
Dual Stream		Each channel can set main stream and sub stream
Video Standard		1080P(1920×1080)30fps / 960P(1280×960)30ftp/720P(1280×720)30fps
Monitoring Image Quality		1080P(1920×1080) / 960P(1280×960)/720P(1280×720)
Image Motion Detection		Each screen can set multiple detection areas and set 6-level sensitivity
Recording Playback Quality		Any 9ch 960P/720P playback, 4ch 1080P/3MP/5MP playbacl simultaneously
Region Cover		Every channel can set 4 cover regions (IPC Support)
Recording Mode		Support manual , auto, dynamic detection, alarm trigger record mode
Backup Way		Support U disk, USB mobile HDD, USB DVD-RW, network storage and
Operation Way		Mouse, Keyboard
Local Login		Username and password
Recording Storage		Local HDD, network
External Ports	Video Input	① 36x(1280*960)+sub(640*360)+4Ref.+9Play 36ch 1.3MP IP Camera
		② 25x(1920*1080)+sub(720*576)+4Ref.+4Play 25ch 2.0MP IP Camera
		③ 16x(2048*1536)+sub(960*576)+4Ref.+4Play 16ch 3.0MP IP Camera
		④ 16x(2592*1944)+sub(960*576)+4Ref.+1Play 16ch 5.0MP IP Camera
	Audio Input	36/25ch network audio input
	Video Output	1ch VGA+1ch HDMI
	Audio Output	1ch RCA output
	Network Port	1 RJ45,10M/100M/1000M self-adaptive LAN port
	RS485 Port	Full duplex standard 485 port
	USB Port	1USB 3.0 port, 2 USB 2.0 ports
Alarm Input	4ch	
Alarm Output	1ch	
Wireless Port	WIFI	
HDD	HDD Port	4 SATA+1 E-SATA HDD ports
	MAX Capacity	Each port supports MAX 4TB HDD
Mobile Surveillance		Support( iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone
Power Supply		12V6A

Working Temperature	-10°C~ +55°C
Working Humidity	10%-90%
Dimension	Equipment: 440x360x70mm, Packing: 460mmx135mmx560 mm
Weight(without HDD)	N.W.: 5.7Kg; with packing: 6.9Kg
Outside Carton	4pcs/carton. 480mmx560x575mm; weight: 30Kg
Installation Way	Desktop Installation





