

AEVISION®



36CH 4K/5MP/1080P 4HDD NVR

- ◆ Support for H. 265/H.264 encoding format streaming access and decoding output; embedded LINUX operation system;
- ◆ Support ONVIF protocol, support High profile S, High profile G, compatible with different IP camera that based on ONVIF, RTSP standard;
- ◆ Support sync video recording, playback, remote monitoring, backup;
- ◆ VGA/HDMI sync output, support 4K UHD preview;



Model Number		N6000-36EX
Operating System		Embedded LINUX operating system
Image Code Control		Image code quality adjustable, variable bitstream and constant bitstream
Dual Stream		Each channel can set main stream and sub stream
Video Standard		H.265/H.264
Monitoring Image Quality		4K / 5MP / 3MP / 1080P / 960P / 720P
Image Motion Detection		Each screen can set multiple detection areas and set 6-level sensitivity
Recording Playback Quality		Any 4ch 4K playback/ 9ch 5MP playback /16ch 1080 playback simultaneously
Region Cover		Every channel can set 4 cover regions (IPC Support)
Recording Mode		Support manual , auto, dynamic detection, alarm trigger record mode
Backup Way		Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup (Partly needs IPC Support)
Operation Way		Mouse, Keyboard
Local Login		Username and password
Recording Storage		Local HDD, network
External Ports	Video Input	① 36x(3840*2160)+sub(960*576)+4Ref.+4Play H.265 8M/ch 36ch 4K IP Camera
		② 36x(2592*1944)+sub(960*576)+4Ref.+9Play H.265 8M/ch 36ch 5MP IP Camera
		③ 36x(1920*1080)+sub(960*576)+4Ref.+16Play H.265 4M/ch 36ch 2MP IP Camera
	Audio Input	36ch network audio input
	Video Output	1ch VGA+1ch HDMI
	Audio Output	1ch RCA output
	NetworkPort	1 RJ45,10M/100M/1000M self-adaptive LAN port
	RS485 Port	Full duplex standard 485 port
	USBPort	1USB 3.0 port, 2 USB 2.0 ports
	Alarm Input	4ch
Alarm Output	1ch	
WirelessPort	WIFI	
HDD	HDDPort	4 SATA HDD ports
	MAX Capacity	Each port supports MAX 4TB HDD
Mobile Surveillance		Support(iPhone, Windows Mobile, BlackBerr, Symbian, Android) smart phone

Power Consumption	≤25W (without HDD)
Working Temperature	-10°C~ +55°C
Working Humidity	10%-90%
Dimension	Equipment: 440×360×70mm, Packing: 460mm×135mm×560 mm
Weight(without HDD)	N.W.: 5.7Kg; with packing: 6.9Kg
Outside Carton	4pcs/carton. 480mm×560×575mm; weight: 30Kg
Installation Way	Desktop Installation



