

AEVISION®

9CH 3MP/4CH 5MP 2HDD

- P2P cloud service, including cloud connecting, cloud monitoring,
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard
- Support megapixel HD network video preview, storage and playback;
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream, and 4 channels playback;



Model Number		AE-N6000-9EH
Operating System		Embedded LINUX operating system
Image Code Control		Image code quality adjustable, variable bitstream and constant bitstream option
Dual Stream		Each channel can set main stream and sub stream
Video Standard		1080P(1920×1080)30fps/960P/(1280×960)/720P(1280×720)30fps
Monitoring Image Quality		1080P(1920×1080) / 960P/(1280×960)/720P(1280×720)
Image Motion Detection		Each screen can set multiple detection areas and set 6-level sensitivity
Recording Playback Quality		1/4/9ch playback simultaneously
Region Cover		Every channel can set 4 cover regions (IPC Support)
Recording Mode		Support manual , auto, dynamic detection, alarm trigger record mode(Partly need)
Backup Way		Support U disk, USB mobile HDD, USB DVD-RW. network storage and backup
Operation Way		Mouse
Local Login		Username and password
Recording Storage		Local HDD, network
External Ports	Video Input	①9×(1280*960)+sub(720*576)+4Ref.+9Play 9ch 1.3MP IP Camera
		②9×(2048*1536)+sub(960*576)+4Ref.+4Play 9ch 3.0MP IP Camera
		③9×(2592*1944)+sub(960*576)+4Ref.+1Play 9ch 5.0MP IP Camera
		/
	Audio Input	9ch network audio input
	Video Output	1ch VGA+1ch HDMI
	Audio Output	1ch RCA output
	Network Port	1 RJ45,10M/100M/1000M self-adaptive LAN port
	Alarm Input	2ch(Optional)
Alarm Output	1ch(Optional)	
USB Port	3 USB 2.0 ports	
Wireless Port	WIFI	
HDD	HDD Port	2 SATA HDD Ports
	MAX Capacity	Each port supports MAX 4TB HDD
Mobile Surveillance		Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone
Power Supply		12V3A
Power Consumption		≤20W (without HDD)

Working Humidity	10%-90%
Dimension	Equipment : 350mm×240mm×70mm, Packing : 409mm×365mm×129mm
Weight(without HDD)	N.W. : 1.7Kg ; With packing : 2.9Kg
Outside Carton	5 pcs/carton. 675mm×425mm×385mm ; Weight : 15.3 Kg
Installation Way	Desktop Installation
Dimension	Equipment : 260mm×220mm×43mm, Packing : 355mm×255mm×88.5mm
Weight(without HDD)	N.W. : 1.5Kg ; With packing : 2.4Kg
Outside Carton	10 pcs/carton. 525mm×455mm×365mm ; Weight : 25 Kg
Installation Way	Desktop Installation

