

# AEVISION®



## 4CH 5MP POE 1HDD

- P2P cloud service, including cloud connecting, cloud monitoring,
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard
- Support megapixel HD network video preview, storage and playback;
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream, and 4 channels playback;



<b>Model Number</b>		<b>AE-N6100-4EH-8P/48</b>
Operating System		Embedded LINUX operating system
Image Code Control		Image code quality adjustable, variable bitstream and constant bitstream
Dual Stream		Each channel can set main stream and sub stream
Video Standard		1080P(1920×1080)30fps/960P/(1280×960)/720P(1280×720)30fps
Monitoring Image Quality		1080P(1920×1080) / 960P/(1280×960)/720P(1280×720)
Image Motion Detection		Each screen can set mutiple detection areas and set 6-level sensitivity (IPC)
Recording Playback Quality		1/4/8ch playback simultaneously
Region Cover		Every channel can set 4 cover regions (IPC Support)
Recording Mode		Support manual , auto, dynamic detection, alarm trigger record mode(Partly)
Backup Way		Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup
Operation Way		Mouse
Local Login		Username and password
Recording Storage		Local HDD, network
External Ports	Video Input	① 4x(2048*1536) +sub(960*576)+4Ref.+4Play 4ch 3.0MP IP Camera
		② 4x(2592*1944)+sub(960*576)+4Ref.+1Play 4ch 5.0MP IP Camera
		/
		/
	Audio Input	4ch network audio input
	Video Output	1ch VGA+1ch HDMI
	Audio Output	1ch RCA Output
	Network Port	1 RJ45, 10/100M self-adaptive LAN port
	USB Port	2 USB 2.0 ports
	Alarm Input	2ch(Optional)
Alarm Output	1ch(Optional)	
Wireless Port	WIFI	
HDD & POE	HDD Port	1 SATA HDD Port
	MAX Capacity	Each port supports MAX 4TB HDD
	POE Port	4 10/100M Independent LAN port, data transferring and power supply both by
	Consumption	52W
	Standard	IEEE802.3af

Power Supply	DC48V2A
Power Consumption	≤115W (without HDD)
Working Temperature	-10°C~ +55°C
Working Humidity	10%-90%
Dimension	Equipment : 260mm×220mm×43mm, Packing : 355mm×255mm×88.5mm
Weight(without HDD)	N.W. : 1.5Kg ; With packing : 2.4Kg
Outside Carton	10 pcs/carton. 525mm×455mm×365mm ; Weight : 25 Kg
Installation Way	Desktop Installation

