

# KPC139EA-H

## H.R. 35 IR LEDs Camera



### ● FEATURES

- (1) High resolution of 600 TV Lines
- (2) High sensitivity in the dark environment, 0.1 Lux / F2.0, 0 Lux (IR ON)
- (3) Day and night features for 24-hour surveillance
- (4) Excellent image quality
- (5) IR distance: up to 25 meters with 35 IR LEDs
- (6) IP67, suitable for outdoor use

### ● SPECIFICATIONS\*

MODEL	KPC139EA-H	
Pick-up Element	1/3" H.R. Color CCD image sensor	
Number of Pixels	768(H) x 494(V) <NTSC> / 752(H) x 582(V) <PAL>	
Resolution	600 TVL	
Min. Illumination	0.1 Lux / F2.0, 0 Lux (IR ON)	0.05 Lux / F2.0, 0 Lux (IR ON)
IR LED	35 units	
IR Effective Range	25 Meters	
S/N Ratio	More than 48dB (AGC off)	
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.	
Lens	f3.6mm / F2.0	f6.0mm / F1.4
Lens Angle	92.6°	54°
White Balance	ATW	
AGC	Auto	
IRIS Mode	AES	
IP Rating	IP67	
Video Output	1.0 Vp-p composite, 75Ω	
Operating Temperature	0°C~40°C	
Power Source (±10%)	DC12V	
Current Consumption (±10%)	70mA (IR OFF), 400mA (IR ON)	
Gross Weight (g)	430	
Dimensions (mm)**	142(H) x 75(Φ)	

\* The specifications are subject to change without notice.

\*\* Dimensional Tolerance: ± 5mm

## Good Sensitivity in Low Illumination

KPC13x Series



Conventional



## True Color

KPC13x Series



Conventional

